

Instructions for Bluebird One Top Box LED Light Panel

- 1) Remove top box display glass to expose florescent, large white deflector tray and power distribution panel.
- 2) Remove Light Pro panel #70-36590-00 from box and remove plastic protective coverings from each side of panel. Check for damage.
- 3) Power down game and remove florescent.
- 4) Connect Suzo-Happ power adaptor cable #70-0217-00 to the cable end of the #70-36590-00 Suzo-Happ LED Light Pro panel.
- 5) Connect the power adaptor cable to the 8-pin connector on the power distribution panel.
- 6) Turn on game to identify bright side of panel and proper operation.
- 7) Power game down
- 8) Take the dual sided foam tape provided in the box to make four 2” pieces. The panel includes approximately 30” of two sided foam tape for additional installations.
- 9) Attach the four 2” foam strips two the rear corners of the LED panel.
- 10) Remove the protective cover strips from the foam adhesive tape strips.
- 11) Position the LED panel and attach to the upper portion of the white light reflector tray.
Installing at the very top enhances the LED light illumination across the entire glass.
- 12) Turn on game and check of proper operation.
- 13) Re-install top box glass

Thank-You for purchasing the Suzo-Happ Light Pro LED Panel.

Check out our full line of LED panels @ suzohapp.com or contact your sales representative.