

MATERIAL SAFETY DATA SHEET

PRODUCT IDENTITY: Tweenen Ten Minute Cement

SECTION I - PRODUCT IDENTIFICATION

DISTRIBUTER:

Tweeten Fibre Co., INC.
 1756 W. Hubbard Street
 Chicago, Illinois 60622

Emergency Phone: (312) 733-7878
Information Phone: (312) 733-7878
DATE ISSUED: 01/19/93

CHEMICAL NAME AND SYNONYMS: None
CHEMICAL FAMILY: Protein Adhesive
COMMON NAME: Wood Adhesive

SECTION II - HAZARDOUS INGREDIENTS

<u>MATERIAL</u>	<u>%</u>	<u>TLV mg/M³</u>	<u>PEL mg/M³</u>	<u>CAS No.</u>
-----------------	----------	---------------------------------	---------------------------------	----------------

(No hazardous ingredients known at this time)

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT:	212 degrees Fahrenheit
EVAPORATION RATE:	Slower than n-Butyl Acetate
VOLATILES WEIGHT:	55%
VAPOR DENSITY:	Lighter than Air
LIQUID DENSITY:	Heavier than Water
WEIGHT PER GALLON:	9.75 pounds
SPECIFIC GRAVITY (H₂O=1):	1.17
APPEARANCE AND ODOR:	Brown color; no V.O.C.s

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	None
EXTINGUISHING MEDIA:	Water, foam, carbon dioxide or dry chem
SPECIAL FIRE FIGHTING PROCEDURES:	Wear positive pressure self-contained NIOSH approved breathing equipment.
UNUSUAL FIRE & EXPLOSION HAZARDS:	Sealed container may rupture. Keep cool with water.

SECTION V - REACTIVITY DATA

STABILITY: Stable
INCOMPATIBILITY: Strong oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS: CO2 & CO
HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE: Vapors may cause eye and respiratory irritation. Liquid contact with eyes or skin may cause irritation.

FIRST AID:

INHALATION: Remove to fresh air.
EYE CONTACT: Flush with water for 15 minutes with lids open. Seek medical attention.
SKIN CONTACT: Remove contaminated clothing. Wash affected area with soap and water.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Ventilate area. Spill area will be slippery. Contain spill. Recover as much as possible for reuse. Spread commercial absorbent over remainder and place into sealed containers for disposal.

WASTE DISPOSAL METHOD: Dispose in accordance with local, state and federal regulations. Most states prohibit disposal of liquids in landfills.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: Usually not required. However, for confined areas or areas with poor ventilation, use an organic vapors cartridge type distributor.

VENTILATION: Mechanically exhaust vapors at point(s) of application. If applicable, maintain airborne contaminant levels of chemicals below their recommended TLVs. (see section II)

PROTECTIVE GLOVES: Impervious.

RESPIRATORY PROTECTION: splash goggles.

MSDS FOR TWEETEN TEN MINUTE CEMENT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Wash thoroughly before eating or smoking.

OTHER PRECAUTIONS:

As with all chemicals, good industrial hygiene and proper work habits should be observed.

DISCLAIMER: The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Since the use of this information, these opinions and the conditions of use of the product are not within the control of Tweeten Fibre Company, Inc., it is the user's obligation to determine the conditions of safe use of the product.

+++++ END OF MSDS FOR TWEETEN TEN MINUTE CEMENT +++++