

MATERIAL SAFETY DATA SHEET

K01371
01 00

MANUFACTURER'S NAME
KRYLON HARDWARE
31500 Solon Rd.
Solon, OH 44139

EMERGENCY TELEPHONE NO.
(216) 292-7400

DATE OF PREPARATION
12-MAY-94

INFORMATION TELEPHONE NO.
(800) 832-2541

=====
Section I -- PRODUCT IDENTIFICATION
=====

PRODUCT NUMBER	K01371	HMIS CODES	
		Health	2
		Flammability	4
		Reactivity	0

PRODUCT NAME
RED OXIDE SANDABLE PRIMER

PRODUCT CLASS
Aerosol Coating

=====
Section II -- HAZARDOUS INGREDIENTS
=====

INGREDIENT CAS No.	% by WT	ACGIH TLV	OSHA PEL	UNITS	V.P.
Propane 74-98-6	16		1000	PPM	760.00
Lt. Aliphatic Hydrocarbon Solvent 64742-89-8	1	100	100	PPM	53.00
Med. Aliphatic Hydrocarbon Solven 64742-88-7	1	Not Established			2.00
Xylene. 1330-20-7	21	100	100	PPM	5.90
	STEL	150	150	PPM	
2-Methyl-1-propanol 78-83-1	1	50	50	PPM	8.70
Acetone. 67-64-1	42	750	750	PPM	180.00
	STEL	1000	1000	PPM	
Talc 14807-96-6	5	2	2	MG/M3 as Resp. Dust	

=====
Section III -- PHYSICAL DATA
=====

PRODUCT WEIGHT -- 6.69 lb./gal. EVAPORATION RATE -- Faster than Ether
 SPECIFIC GRAVITY -- 0.81 VAPOR DENSITY -- Heavier than Air
 BOILING POINT -- <0 -343 F MELTING POINT -- N.A.
 VOLATILE VOLUME -- 91 % SOLUBILITY IN WATER -- N.A.
 VOLATILE WEIGHT -- 82.01 % (less Federally Exempt Solvents)
 HMIS -- 2 4 0

=====
Section IV -- FIRE AND EXPLOSION HAZARD DATA
=====

FLASH POINT	LEL	UEL
Propellant < 0 F	1.0	12.8

EXTINGUISHING MEDIA
Carbon Dioxide, Dry Chemical, Foam

Continued on page 2

HAZARDOUS POLYMERIZATION

Will not occur

Section VII -- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert sorbent.

STE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section VIII -- PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section II) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section II, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m3 (total dust), OSHA PEL 15 mg./m3 (total dust), 5 mg./m3 (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Section IX -- PRECAUTIONS

DOL STORAGE CATEGORY

1A